R	EFRIGERATORS				
		1896	1897	1898 / 1958	1899 / 1959
FE	ATURES & SPECIFICATIONS	Bottom	Side-by-Side	French Door	French Door
		Mount		Full Depth	Counter Depth
C/	APACITY				
	al Fridge & Freezer (cu. ft.)	18.5	25.6	24.8	19.8
	al Fridge (cu. ft.)	12.9	16.0	17.5	14.4
Tot	al Freezer (cu. ft.)	5.6	9.6	7.3	5.4
RE	FRIGERATOR / FREEZER FEATURES				
Ful	ly adustable shelving	*	*	*	*
Ga	llon size adjustable door storage	*	*	*	*
	aled vegetable crisper with adjustable humidity control	*	*	*	*
De	li bin with adjustable temperature control		*	*	*
Cri	spers and bins made of clear durable Lexan™	*	*	*	*
Be	verage rack		*		
Sli	de out upper freezer basket	*		*	*
Se	parate fridge / freezer controls	*	*	*	*
Sm	nartWater™ ice / water filtration system through door		*		
Int	ernal filtered water dispenser			*	*
	ctory installed ice maker	Optional	Standard	Standard	Standard
En	ergyStar	*	*	*	*
En	erguide rating (KwH/year)	448	583	505	451
	ipping weight (lb.)	370	460	460	400
CA	ABINET FEATURES				
Ini	ection molded fiberglass doors with enamel coating	•	•	•	•
,	justable rollers provide easy movement for cleaning	•		•	•
	ulptured door handles	•	•	•	•
	il free back, clean-free condenser	•		•	•
	ft hand hinge	Optional	N/A	N/A	N/A
		o p a consu			
CC	DLORS				
Sta	andard - Black, White, Bisque	•	•	•	•
	emium - Cayenne Pepper Red, Liberty Blue			•	•
	andard Door Handles	Nickel	Nickel	Nickel/Chrome	Nickel/Chrome
	tique Brass or Antique Copper door handles	Optional	Optional	Optional / N/A	Optional / N/A
	kel, Antique Brass or Antique Copper door frames	Optional	Optional	Optional / N/A	Optional / N/A
	, ,				
DII	MENSIONS				
Α	Height to top of door	67-1/4"	69-3/4"	69-7/8" / 72-3/16"	69-7/8" / 72-3/16"
	Height to top of hinge	66-1/2"	69-3/8"	69-7/8" / N/A	69-7/8" / N/A
В	Height to top of case*	65-3/4"	68-3/4"	68-5/8" / 71-15/16"	68-5/8" / 71-15/16"
С	Depth not including door	28-1/4"	28"	29"	24"
D	Depth inlcuding door	33-3/4"	34"	34"/36"	29"/31"
E	Depth including door and handles	33-3/4"	34-1/2"	35-3/8" / 38	30-3/8" / 33"
F		59-1/2"	50-1/2"	48-1/4"	43-1/4"
G	Depth with freezer drawer open	52-1/2"	N/A	54-3/4" / 57"	46" / 48-1/4"
Н	Width of case	29-1/4"	35-3/4"	35-5/8"	35-5/8"
1	Width with door(s)	30"	36-3/8"	36"	36"
	Width with door(s) open 90 degrees (not inc. handle)	32-1/4"	39-1/2"	42-7/8" / 46-7/8"	42-7/8" / 46-7/8"
	Side clearance from wall for doors to open 90 degrees	2-1/2"	4"	4" / 6"	4"/6"
Cu	tout dimensions:	- I/-	·	. , 5	. , 5
Cu	Width	30"	37 "	36"	36"
	Height	67"	70"	70" / 73"	70" / 73"
	Minimum depth	24"	24"	24"	24"
	Ideal depth	28"	28"	28"	24"
	racar acptir	20	20	20	LT

^{*}Case cap can be removed on Models 1958 / 1959 – reduces case height by 3-5/16*, to 68-5/8*. Height to top of hinge with cap removed is 69-3/8*. (If necessary, allow clearance over fridge doors for overhead cabinet door swings.)

MICROWAVES & WALL OVENS

FEATURES & SPECIFICATIONS 1895 18			
	Microwave	Wall Oven	
CAPACITY	2.0 cu. ft.	5.0 cu. ft.	
DIMENSIONS			
Overall Dimensions:			
Height	14"	30-1/4"	
Width	24"	30"	
Depth	20"	28"	
Depth with Doors, Ash Catch		33-1/2"	
Cabinet Cut-Out Dimensions (Minimum):			
Height	14-1/4"	28"	
Width	24-1/4"	28-1/2"	
Cabinet Width		30"	
Depth	24"	24"	
Rear Stop Depth	15-1/2"	N/A	
Power Source	120V, 15A	220V, 30A	
Shipping Weight	65 lb.	200 lb.	
Wall Oven Notes:			
Allow 5-1/4" minimum from bottom of cutout to floor.			
Allow 1-1/2" minimum from top of cutout to underside of countertop.			
Wall ovens can be installed two high.			
8			

REFRIGERATOR DIMENSIONS



